

**Bona Underlayments – Solutions for reducing stepping sounds and for strengthening weak surfaces.**

Bona's underlayments provide extra features to the floor, reducing the stepping sound and giving the floor a softer, more exclusive feel. Underlayments can also be used as a problemsolver on concrete floors with cracks and weak, porous surfaces. The latter problem is quite common and widespread among many old floors.

Underlayments provide extra sound insulation and strengthen weak surfaces. From a sales point of view, selling in an underlayment will automatically generate higher adhesives sales as you will need to use adhesive both on top and below the underlayment to fix your wooden floor.

Bona offers three different types of underlayments: **U300, U310 and U340.**

## **Bona U300**

Article Number: AX36225002/5003/5005

Bona U300 is an underlayment for reducing impact sound from footsteps. It is based on a cork/rubber mix and available in 2, 3 and 5mm thicknesses.

### Gross price/m<sup>2</sup>

Bona U300 Cork Rubber 2mm (1.0 x 30 m)

Bona U300 Cork Rubber 3mm (1.0 x 20 m)

Bona U300 Cork Rubber 5mm (1.0 x 16 m)

The following adhesives are recommended:

Bona R850 / R850T / R860 and

Bona R770 / R777 / R778

## Bona U310

Article Number: AX36310003

Bona U310 is an underlayment designed for strengthening weak surfaces. It is a thin fleece sheet, based on spun polyester. With a thickness of just 1 mm you are able to use it almost everywhere without affecting the floors height limitations. The material will be delivered in rolls (1 m x 50 m)

The following adhesives are recommended:

Bona R770 / R777 / R778

Bona R844 / R845 / R850 / R850T / R860 / R870T

The use of the Bona dispersion adhesives Bona D705 and D720 is also possible. However, because of their short open time they are much more difficult to work with.

Gross price/m<sup>2</sup>

Bona U310 (50 m<sup>2</sup> on a roll)

## Bona U340

AX36340004

Bona U340 – A fibre-reinforced polyester board for powerful strengthening of weak surfaces and for heat insulation. Available in 4 and 9 mm thickness. This type of underlayment is not recommended for underfloor heating systems because of its high thermal resistance except under special circumstances and then in combination with the 4 mm thick board together with multi-layered parquet. Dimension of the boards: 1000 x 600 mm

The following adhesives are recommended:

Bona R770 / R777 / R778

Bona R844 / R845 / R850 / R850T / R860

Gross price/m<sup>2</sup>

Bona U340 4mm

The different underlayments:

