



NOVILON AUTHENTIC & SELECT

SUGGESTED SPECIFICATION_

NOVILON AUTHENTIC

Supply and fix 1.50mm thick x 2.0m wide Novilon Authentic sheeting, manufactured in accordance with EN 653 and laid in FloorworX No. 62 acrylic adhesive which has been spread using a trowel fitted with an A2 notched blade at a rate of between 5.5m² and 6.5m² per litre on a previously prepared Class 1 sub-floor in accordance with SANS 10070, using FloorworX Self Leveller when required, including all cutting and waste. The sheeting must be rolled in both directions with an articulated 68kg three-sectional roller immediately after it has been laid into the adhesive. Joins must be welded with Noviweld solvent weld, especially around water points such as baths, basis, toilets and laundries.

NOVILON SELECT

Supply and fix 2.60mm thick x 2.0m wide Novilon Select sheeting, manufactured in accordance with EN 653 and laid in FloorworX No. 62 acrylic adhesive which has been spread using a trowel fitted with an A2 notched blade at a rate of between 5.5m² and 6.5m² per litre on a previously prepared Class 1 sub-floor in accordance with SANS 10070, using FloorworX Self Leveller when required, including all cutting and waste. The sheeting must be rolled in both directions with an articulated 68kg three-sectional roller immediately after it has been laid into the adhesive. Joins must be welded with Noviweld solvent weld, especially around water points such as baths, basis, toilets and laundries.

