



Total Thickness	ISO 24346 (EN 428)	2.5mm
Dimensions		Rolls: 2m x 20m
Dimensions		Welding Rod: ± Ø4.3mm x 50m
Packaging	ISO 24241 (EN 426)	40m ² Per Roll
Total Weight	ISO 23997 (EN 430)	4.6kg/m ²
Colour Range		18 Selected Colours
Use Classification	ISO 10874 (EN 685)	Class 34 Commercial - Very Heavy
	ISO 10874 (EN 685)	Class 43 Industrial - Heavy
Reaction to Fire	EN ISO 13501-1 EN ISO 9239-1 EN ISO 11925-2	Br1 - S1 ≥ 8 kW/m ² Pass SR*
Dimensional Stability	ISO 23999 (EN 434)	≤ 0.40%
Castor Wheel Test	ISO 4918 (EN 425)	Pass SR*
Residual Indentation	ISO 24343-1 (EN 433)	± 0.10mm
Slip Resistance	DIN 51130	R9
Slip Resistance	EN 13893	Class DS μ ≥ 0.3
Fungi And Bacteria Resistance	ISO 846: PART C	Does not favour growth.
Static Electrical Charge	EN 1815	< 2kV
Light Fastness	EN ISO 105-B02	≥ Level 6
Thermal Resistance	EN 12667	± 0.01m ² k/W
Underfloor Heating		Suitable provided that the temperature of the surface of the sub-floor does not exceed 27°C.
Surface Treatment		PUR
Emissions	ISO 16000-6	≤ 10μg/m ³ (TVOC after 28 Days)
Marine Equipment	IMO FTPS Part 5 and 2 IMO Res. A653	O575 O575
CE Conformity	EN 14041	Pass SR*
Seam Strength	EN 684	Average: ≥ 240 N/50mm Individual: ≥ 180 N/50mm

SR* = Standard Requirements



It is advised to confirm stock availability on **0860 346 679**