



| | | |
|--------------------------------------|---------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Total Thickness | | 2.0mm |
| Dimensions | | Rolls: 2m x 23m |
| Dimensions | | Tiles: 610mm x 610mm (Special Order) |
| Dimensions | | Welding Rod: ± Ø4.3mm x 50m |
| Packaging | | 46m ² Per Roll 16 Tiles Per Box (5.95m ²) |
| Total Weight | | 3.0kg/m ² |
| Colour Range | | 18 Selected Colours (Classic) 36 Selected Colours (Spirit) |
| Use Classification | ISO 10581 (EN 649) | Class 34 Commercial - Very Heavy |
| | ISO 10581 (EN 649) | Class 43 Industrial - Heavy |
| Reaction to Fire | EN ISO 13501-1 EN ISO 9239-1 EN ISO 11925-2 | Bi - S1 ≥ 8 kW/m ² Pass SR* |
| Flexibility | EN 435 | Pass SR* |
| Dimensional Stability | ISO 23999 (EN 434) ISO 23999 (EN 434) | Rolls: ≤ 0.40% Tiles: ≤ 0.25% |
| Castor Wheel Test | ISO 4918 (EN 425) | Pass SR* |
| Residual Indentation | ISO 24343-1 (EN 433) | ≤ 0.10mm |
| Abrasion Resistance | EN 660: PART 2 | Group T* |
| Slip Resistance | DIN 51130 | R9 |
| Slip Resistance | EN 13893 | Class DS μ ≥ 0.3 |
| Fungi And Bacteria Resistance | ISO 26987 (EN 423) | Does not favour growth. |
| Chemical Resistance | ISO 846: PART C | Good resistance to everyday substances. Advice is available on resistance to specific chemicals and dilutions. |
| Static Electrical Charge | EN 1815 | < 2kV |
| Light Fastness | EN ISO 105-B02 | ≥ Level 6 |
| Thermal Resistance | EN 12667 | 0.01m ² k/W |
| Underfloor Heating | DIN 51130 | Suitable provided that the temperature of the surface of the sub-floor does not exceed 27°C. |
| Surface Treatment | | PUR |
| Emissions | | < 10μg/m ³ (TVOC after 28 Days) |
| CE Conformity | EN 14041 | Pass SR* |
| Clean Room Test | ASTM F51/00 | Class A |

SR* = Standard Requirements

T* = Confirmation of revised abrasion performance

Available in half rolls subject to a cutting surcharge (ex-stock items only). A surcharge will be levied on quantities less than 200m² unless product is available ex-stock.



It is advised to confirm stock availability on **0860 346 679**