



<b>Total Thickness</b>		1.6mm      2.0mm      2.5mm
<b>Dimensions</b>		<b>Tiles:</b> 300mm x 300mm
<b>Packaging</b>		<b>1.6mm:</b> 75 Tiles Per Box (6.75m <sup>2</sup> ) <b>2.0mm:</b> 50 Tiles Per Box (4.5m <sup>2</sup> ) <b>2.5mm:</b> 50 Tiles Per Box (4.5m <sup>2</sup> )
<b>Total Weight</b>		<b>1.6mm:</b> 3.7kg/m <sup>2</sup> <b>2.0mm:</b> 4.5kg/m <sup>2</sup> <b>2.5mm:</b> 5.4kg/m <sup>2</sup>
<b>Colour Range</b>		18 Selected Colours 2 Plain Colours - available on request
<b>Reaction to Fire</b>	SANS 0177	Part 4 - Class 1
<b>Indentation</b>	SANS 581	Pass (Suitable for intensive use)
<b>Residual Indentation</b>	SANS 581	Pass (Excellent recovery from indentation)
<b>Chemical Resistance</b>		Good resistance to everyday substances. Advice is available on resistance to specific chemicals and dilutions.
<b>Static Electrical Charge</b>		Classified as electrically insulating. Not conductive or anti-static in nature.
<b>Underfloor Heating</b>		Suitable provided that the temperature of the surface of the sub-floor does not exceed 27°C.
<b>Emissions</b>	GREEN BUILDING SPECIFICATIONS	0.01µg/m <sup>3</sup> /hour

SR\* = Standard Requirements



It is advised to confirm stock availability on **0860 346 679**

