GYMFIT 50
> PRODUCT DATA

Total Thickness		5.0mm
Dimensions		**Rolls:** 2m x 15m to 25m
Dimensions		**Welding Rod:** Ø4.5mm x 70m
Packaging		30m² to 50m² Per Roll
Total Weight		2.9kg/m²
Colour Range		8 Selected Colours
Reaction to Fire	EN 13501	C_{fl} - s1
Dimensional Stability	ISO 23999	0.2%
Resistance to Rolling Load	EN 1569	1500N
Friction	EN 13036-4	80 - 110
Shock Absorption	EN 14808	31%
Vertical Deformation	EN 14809	0.33mm
Ball Rebound	EN 12235	100%
Specular Gloss	EN ISO 2813	< 30%
Residual Indentation	EN 1516	< 0.2mm
Abrasion Resistance	EN ISO 5470-1	Group T
Chemical Resistance	EN ISO 26987	Pass SR*
Light Fastness	EN ISO 105-B02	Level 6
Thermal Resistance		0.045m² k/W
Underfloor Heating	DIN 51130	Suitable provided that the temperature of the surface of the sub-floor does not exceed 27°C.
Sound Absorption	EN ISO 717-2	ΔLw = 16dB
Surface Treatment		PUR
Emissions	Formaldehyde Pentachlorphenol	No Formaldehyde No Pentachlorphenol

SR* = Standard Requirements

It is advised to confirm stock availability on **0860 346 679**