



Total Thickness		2.0mm 2.5mm
Wear Layer Thickness		2.0mm: 1.0mm 2.5mm: 1.5mm
Dimensions		Rolls: 2m x 30m to 32m
Dimensions		Welding Rod: ± Ø4.30mm x 50m
Packaging		60m ² to 64m ² Per Roll
Total Weight		2.0mm: 2.3kg/m ² 2.5mm: 2.9kg/m ²
Colour Range		38 Selected Colours
Use Classification	EN 685	2.0mm: Class 32 Commercial - General 2.0mm: Class 41 Industrial - Moderate 2.5mm: Class 34 Commercial - Very Heavy 2.5mm: Class 43 Industrial - Heavy
Reaction to Fire	EN ISO 13501-1	CrI - S1
Flexibility	ISO 24344 (EN 435)	2.0mm: Ø30mm 2.5mm: Ø40mm
Castor Wheel Test	ISO 4918 (EN 425)	Pass SR*
Residual Indentation	ISO 24343-1 (EN 433)	2.0mm: 0.07mm 2.5mm: 0.08mm
Slip Resistance	DIN 51130 (EN 13036-4)	R9
Slip Resistance	EN 13893	Class DS $\mu \geq 0.3$
Bacteriostatic		marmoleum® has fungistatic and bacteriostatic treatments.
Stain Resistance	EN 423 (ISO 26987)	Pass SR*
Burn Mark Resistance	EN 1399	Resistant
Static Electrical Charge	EN 1815	< 2kV
Light Fastness	EN ISO 105-B02	> Level 6
Thermal Resistance	EN 12524	0.17m ² k/W
Underfloor Heating	DIN 51130	Suitable provided that the temperature of the surface of the sub-floor does not exceed 27°C.
Sound Absorption	EN ISO 717-2	2.0mm: ≤ 4dB 2.5mm: ≤ 5dB
Surface Treatment		Topshield 2™
Emissions	EN ISO 16000	< 100µg/m ³ (TVOC after 28 Days)
CE Conformity	EN 14041	Pass SR*
Reach	1907/2006/CE	Compliant

Available in half rolls subject to a cutting surcharge (ex-stock items only).
A surcharge will be levied on quantities less than 200m² unless product is available ex-stock.



It is advised to confirm stock availability on **0860 346 679**

SR* = Standard Requirements