



Total Thickness		2.5mm
Wear Layer Thickness		1.5mm
Dimensions		Rolls: 2m x 30m to 32m
Dimensions		Welding Rod: ± Ø4.30mm x 50m
Packaging		60m² to 64m² Per Roll
Total Weight		2.9kg/m²
Colour Range		8 Selected Colours (Colour) 12 Selected Colours (Original) 7 Selected Colours (Textura)
Use Classification		Class 34 Commercial - Very Heavy Class 42 Industrial - General
Reaction to Fire	EN ISO 13501-1	Cfl - S1
Flexibility	ISO 24344 (EN 435)	Ø40mm
Castor Wheel Test	ISO 4918 (EN 425)	Pass SR*
Residual Indentation	ISO 24343-1 (EN 433)	0.08mm
Slip Resistance	DIN 51130 (EN 13036-4)	R9
Slip Resistance	EN 13893	Class DS $\mu \geq 0.3$
Bacteriostatic		marmoleum® has fungistatic and bacteriostatic treatments.
Stain Resistance	EN 423 (ISO 26987)	Pass SR*
Burn Mark Resistance		Resistant
Static Electrical Charge	EN 1815	< 2kV
Light Fastness	EN ISO 105-B02	> Level 6
Thermal Resistance	EN 12524	0.17m² k/W
Underfloor Heating	DIN 51130	Suitable provided that the temperature of the surface of the sub-floor does not exceed 27°C.
Sound Absorption	EN ISO 717-2	$\Delta L_w = 7dB$
Surface Treatment		Topshield 2™
Emissions	EN ISO 16000	< 100µg/m³ (TVOC after 28 Days)
CE Conformity	EN 14041	Pass SR*
Reach	1907/2006/CE	Compliant

Available in half rolls subject to a cutting surcharge (ex-stock items only).
A surcharge will be levied on quantities less than 200m² unless product is available ex-stock.



It is advised to confirm stock availability on **0860 346 679**

SR* = Standard Requirements