



<b>Total Thickness</b>		2.6mm
<b>Wear Layer Thickness</b>		0.7mm
<b>Dimensions</b>		<b>Rolls:</b> 2m x 25m
<b>Packaging</b>		50m <sup>2</sup> Per Roll
<b>Total Weight</b>		2.7kg/m <sup>2</sup>
<b>Colour Range</b>		39 Selected Colours
<b>Use Classification</b>	EN-ISO 10874 (EN 651)	Class 34 Commercial - Very Heavy
	EN-ISO 10874 (EN 651)	Class 42 Industrial - General
<b>Reaction to Fire</b>	EN ISO 13501-1	B <sub>fl</sub> - s1 <sup>(2)</sup>
<b>Dimensional Stability</b>	EN-ISO 23999	≤ 0.10%
<b>Castor Wheel Test</b>	ISO 4918 (EN 425)	Pass SR*
<b>Residual Indentation</b>	EN-ISO 24343-1	-0.05mm
<b>Abrasion Resistance</b>	EN 660: PART 2	Group T
<b>Slip Resistance</b>	DIN 51130	R9
<b>Slip Resistance</b>	EN 13893	Class DS $\mu \geq 0.3$
<b>Stain Resistance</b>	EN-ISO 26987	Good
<b>Static Electrical Charge</b>	EN 1815	E ≤ 2kV
<b>Light Fastness</b>	EN ISO 105-B02 Method 3	Level 7
<b>Underfloor Heating</b>	EN 12524 (EN-ISO 10456)	Suitable provided that the temperature of the surface of the sub-floor does not exceed 27°C.
<b>Sound Absorption</b>	EN - ISO 354 EN - ISO 11654	$\alpha_w = \pm 0.05$ $\alpha_w = \pm 0.05$
<b>Impact Sound Reduction</b>	EN ISO 717-2	$\Delta L_w = 15dB$
<b>In-Room Impact Noise</b>	NF S 31-074	$L_{n,e,w} < 65dB$ , Class A
<b>Surface Treatment</b>		PUR
<b>Emissions</b>	EN-ISO 16000-9	< 100 $\mu$ g/m <sup>3</sup> (TVOC after 28 Days)
<b>CE Conformity</b>	EN 14041	Pass SR*
<b>Reach</b>	ISO 16581 (EN 424)	Compliant

<sup>(2)</sup> Valid on non combustible substrate: A2<sub>fl</sub>-s1 or A1<sub>fl</sub>

SR\* = Standard Requirements

Available in full rolls only.



It is advised to confirm stock availability on **0860 346 679**