



<b>Total Thickness</b>		2.0mm
<b>Wear Layer Thickness</b>		0.7mm
<b>Dimensions</b>		<b>Rolls:</b> 2m x 25m
<b>Dimensions</b>		<b>Welding Rod:</b> ± Ø4.3mm x 50m
<b>Packaging</b>		50m <sup>2</sup> Per Roll
<b>Total Weight</b>		2.412kg/m <sup>2</sup>
<b>Colour Range</b>		7 Selected Colours (Uni) 9 Selected Colours (Canyon)
<b>Use Classification</b>	EN 685	Class 34 Commercial - Very Heavy
	EN 685	Class 43 Industrial - Heavy
<b>Reaction to Fire</b>	EN ISO 13501-1	B <sub>fl</sub> - s1
<b>Dimensional Stability</b>	EN 434	≤ 0.10%
<b>Castor Wheel Test</b>	EN 425	Pass SR*
<b>Residual Indentation</b>	EN 433	0.02mm
<b>Abrasion Resistance</b>	EN 660: PART 2	Group T
<b>Slip Resistance</b>	DIN 51130 EN 13845 (A.C)	R9 (Uni) R10 (Canyon)
<b>Stain Resistance</b>	EN 423	Pass SR*
<b>Static Electrical Charge</b>	EN 1815	< 2kV
<b>Light Fastness</b>	EN ISO 105-B02	Level 7
<b>Thermal Resistance</b>	EN 12524	0.25 W/(m.K)
<b>Underfloor Heating</b>	DIN 51130	Suitable provided that the temperature of the surface of the sub-floor does not exceed 27°C.
<b>Sound Absorption</b>	EN ISO 717-2	ΔLw = 5dB
<b>Surface Treatment</b>		OVERCLEAN
<b>Emissions</b>	EN ISO 16000	< 20µg/m <sup>3</sup> (TVOC after 28 Days)
<b>CE Conformity</b>	EN 14041	Pass SR*
<b>Reach</b>	1907/2006/CE	Compliant

SR\* = Standard Requirements  
Available in full rolls only.



It is advised to confirm stock availability on **0860 346 679**