



Total Thickness		2.0mm 2.5mm
Dimensions		Rolls: 1.2m x 15m
Dimensions		Tiles: 300mm x 300mm
Dimensions		Welding Rod: ± Ø4.3mm x 50m
Packaging		2.0mm: 18m ² Per Roll 2.5mm: 18m ² Per Roll 2.0mm: 50 Tiles Per Box (4.5m ²) 2.5mm: 50 Tiles Per Box (4.5m ²)
Total Weight		2.0mm: 3.75kg/m ² 2.5mm: 4.5kg/m ²
Colour Range		16 Selected Colours
Reaction to Fire	SANS 0177	Part 4 - Class 1
Indentation	SANS 786	Pass (Suitable for intensive use)
Abrasion Resistance	EN 660-2	Group M
Chemical Resistance	EN 423	Good resistance to everyday substances. Advice is available on resistance to specific chemicals and dilutions.
Static Electrical Charge		Classified as electrically insulating. Not conductive or anti-static in nature.
Underfloor Heating		Suitable provided that the temperature of the surface of the sub-floor does not exceed 27°C.
Emissions	GREEN BUILDING SPECIFICATIONS	0.03µg/m ² /hour

SR* = Standard Requirements



It is advised to confirm stock availability on **0860 346 679**

