



Total Thickness		2.0mm
Wear Layer Thickness		0.7mm
Dimensions		Rolls: 2m x 20m to 27m
Dimensions		Welding Rod: ± Ø4.3mm x 50m
Packaging		40m ² to 54m ² Per Roll
Total Weight		2.75kg/m ²
Colour Range		33 Selected Colours (Original) 9 Selected Colours (Star)
Use Classification	EN 685	Class 34 Commercial - Very Heavy
	EN 685	Class 43 Industrial - Heavy
Reaction to Fire	EN ISO 13501-1	B _{fl} - s1
Dimensional Stability	EN 434	≤ 0.10%
Castor Wheel Test	EN 425	Pass SR*
Residual Indentation	EN 433	0.02mm
Abrasion Resistance	EN 660: PART 2	Group T
Slip Resistance	DIN 51130	R10
Stain Resistance	EN 423	Pass SR*
Static Electrical Charge	EN 1815	< 2kV
Light Fastness	EN ISO 105-B02	Level 6
Thermal Resistance	EN 12524	0.25 W/(m.K)
Underfloor Heating	DIN 51130	Suitable provided that the temperature of the surface of the sub-floor does not exceed 27°C.
Sound Absorption	EN ISO 717-2	ΔLw = 5dB
Surface Treatment		PUR Pearl™
Emissions	EN ISO 16000	< 25µg/m ³ (TVOC after 28 Days)
CE Conformity	EN 14041	Pass SR*
Reach	1907/2006/CE	Compliant

SR* = Standard Requirements

Available in half rolls subject to a cutting surcharge (ex-stock items only).

A surcharge will be levied on quantities less than 200m² unless product is available ex-stock.



It is advised to confirm stock availability on **0860 346 679**