



Total Thickness		2.0mm
Dimensions		Rolls: 2m x 23m
Dimensions		Tiles: 610mm x 610mm
Dimensions		Welding Rod: ± Ø4.3mm x 50m
Packaging		46m ² Per Roll 16 Tiles Per Box (5.95m ²)
Total Weight		2.85kg/m ²
Colour Range		34 Selected Colours
Use Classification	ISO 10581 (EN 649)	Class 34 Commercial - Very Heavy
	ISO 10581 (EN 649)	Class 43 Industrial - Heavy
UPEC Classification	UPEC NF UPEC A+ CERTIFICATE (REF NF 189)	U4 P3 E2/3 C2 312-024.1
Reaction to Fire	EN ISO 13501-1 EN ISO 9239-1 EN ISO 11925-2	Br - S1 ≥ 8 kW/m ² Pass SR*
Flexibility	EN 435	Pass SR*
Dimensional Stability	ISO 23999 (EN 434)	≤ 0.40%
Castor Wheel Test	ISO 4918 (EN 425)	Pass SR*
Residual Indentation	ISO 24343-1 (EN 433)	≤ 0.10mm
Abrasion Resistance	EN 660: PART 2	Group T*
Slip Resistance	DIN 51130	R9
Slip Resistance	EN 13893	Class DS μ ≥ 0.3
Fungi And Bacteria Resistance	ISO 846: PART C	Does not favour growth.
Chemical Resistance	ISO 26987 (EN 423)	Good resistance to everyday substances. Advice is available on resistance to specific chemicals and dilutions.
Static Electrical Charge	EN 1815	< 2kV
Light Fastness	EN ISO 105-B02	≥ Level 6
Thermal Resistance	EN 12667	0.01m ² k/W
Underfloor Heating	DIN 51130	Suitable provided that the temperature of the surface of the sub-floor does not exceed 27°C.
Surface Treatment		PUR
Emissions		< 10μg/m ³ (TVOC after 28 Days)
CE Conformity	EN 14041	Pass SR*
Clean Room Test	ASTM F51/00 ISO 146 44-1	Class A Class 4

SR* = Standard Requirements

T* = Confirmation of revised abrasion performance



It is advised to confirm stock availability on **0860 346 679**