



Nov 2018

## DATA SHEET NO. 108

### FLOORWORX NO. 33

### BONDING LIQUID

#### DESCRIPTION

**FloorworX No. 33** is a water-based synthetic latex emulsion designed to be used as a primer on power-floated sub-floors or porous screeds or as an additive to FloorworX Pavelite to promote improved bonding of FloorworX Pavelite to the sub-floor.

#### COVERAGE

FloorworX No 33 Bonding Liquid is available in 5-litre and 25-litre containers and covers approximately 10m<sup>2</sup> per litre depending on substrate or surface porosity. Coverage can however be as low as 6-8m<sup>2</sup> per litre on highly porous surfaces.

#### PREPARATION

Ensure that the sub-floor is dry by testing with a suitably approved Concrete Moisture Meter. (*Tramex CME 4, Caisson VI-D4 Pinless Concrete Moisture Meter, GE Protimeter Mini or a Hygrometer*). (See **FloorworX Technical Bulletin No. 30: Moisture in Sub-Floors and Damp-Proof Membranes**).

Screed moisture should not exceed the permissible limit as described in **FloorworX Technical Bulletin No. 30: Moisture in Sub-Floors and Damp- Proof Membranes**"

#### APPLICATION

- Apply FloorworX No. 33 Bonding Liquid with a lambswool applicator or paint roller to the screed. Work in well in both directions.
- Allow to dry for approximately 45 minutes.
- FloorworX No 33 Bonding Liquid should be used as an additive to FloorworX Pavelite, relative to the trafficable area of application. Refer to **Data Sheet No 101 on Pavelite and other Technical Bulletins that reference the use of FloorworX No 33 Bonding Liquid**.

#### CLEANING

FloorworX No. 33 Bonding Liquid should be cleaned off immediately with water.

#### STORAGE

FloorworX No. 33 Bonding Liquid has a shelf life of approximately 18 months when stored between 5°C and 50°C. Protect from freezing.

#### HAZARDS

FloorworX No. 33 Bonding Liquid is classified as non-hazardous and non-flammable.

#### DISCLAIMER

THIS INFORMATION IS BASED ON OUR EXPERTISE AND IS GIVEN IN GOOD FAITH BUT WITHOUT WARRANTY. WE CANNOT ACCEPT LIABILITY FOR ANY DAMAGE, LOSS, OR ACCIDENT CAUSED DIRECTLY OR INDIRECTLY BY THIS PRODUCT.

An Accéntuate Limited Company