



<b>Total Thickness</b>		1.00mm
<b>Wear Layer Thickness</b>		0.10mm
<b>Dimensions</b>		<b>Rolls:</b> 2.0m x 20m 2.0m x 5m (Packs)
<b>Packaging</b>		40m <sup>2</sup> Per Roll 10m <sup>2</sup> Per Pack
<b>Total Weight</b>		1.60kg/m <sup>2</sup>
<b>Colour Range</b>		7 Selected Colours
<b>Use Classification</b>	EN ISO 10874 - EN 685	Class 21 Domestic - Moderate / Light
<b>Abrasion Resistance</b>	EN 660-2	Group T
<b>Light Fastness</b>	EN ISO 105 B-02	≥ 6      Volume Loss < 2mm <sup>3</sup>
<b>Residual Indentation</b>	ISO 24343-1 - EN433	≤ 0.10mm
<b>Castor Wheel Test</b>	ISO 4918 - EN 425	Continuous
<b>Dimensional Stability</b>	ISO 23999 - EN 434	+/- 0.40%
<b>Flexibility</b>	ISO 24344 - EN 435 (20mm Mandrel)	No Cracking
<b>Slip Resistance</b>	DIN 51130	R9
<b>Reaction to Fire</b>	EN 13501-1	Bfl - S1
<b>Electrical Behaviour</b>	EN 1815	< 2kV
<b>Indoor Air Quality</b>	CA Section 01350 (≤ 0.5mg/m <sup>3</sup> ) Floorscore Certified (SCS-FS-04547)	Yes
<b>CE Conformity</b>		Conforms
<b>Surface Treatment</b>		PU Treatment
<b>Flooring Type</b>	EN ISO 10582	Heterogeneous Semi Contact
<b>Binder Content</b>	EN ISO 10582	Type 1

