

 **AREAS OF USE**

EDUCATION
HEALTHCARE



SUGGESTED SPECIFICATION

SUPERFLEX® SHEETING

Supply and fix 2.0mm / 2.5mm thick x 1.2m wide Superflex fully-flexible vinyl sheeting, manufactured in accordance with SANS 786 and laid in FloorworX No. 62 acrylic adhesive which has been spread using a trowel fitted with an A2 notched blade at a rate of between 5.5m² and 6.5m² per litre or FloorworX No. 71 contact adhesive spread using a flat trowel, brush or paint roller at a rate of approximately 3.5m² per litre (single surface application), applied to both the sheeting and the previously prepared Class 1 sub-floor in accordance with SANS 10070, using a reliable Self-Leveller when required, including all cutting and waste. The sheeting must be rolled in both directions with an articulated 68kg three-sectional roller immediately after it has been laid into the adhesive. Joins must be butted, grooved and heat welded using a FloorworX Welding Rod, ensuring that the welding rod bonds to more than 70% of the sheet thickness. The newly laid floor must, after 48 hours, be stripped using FloorworX Stripper, scrubbed using a diluted solution of FloorworX Rinse and then seal with three coats of FloorworX Silk Matt or Gloss Sealer.

SUPERFLEX® TILES

Supply and fix 2.0mm / 2.5mm thick x 300mm x 300mm Superflex fully-flexible vinyl tiles, manufactured in accordance with SANS 786 and laid in FloorworX No. 62 acrylic adhesive which has been spread using a trowel fitted with an A2 notched blade at a rate of between 5.5m² and 6.5m² per litre, on a previously prepared Class 1 sub-floor in accordance with SANS 10070, using a reliable Self-Leveller when required, including all cutting and waste. The flooring must be rolled in both directions with an articulated 68kg three-sectional roller immediately after it has been laid into the adhesive. The newly laid floor must, after 48 hours, be stripped using FloorworX Stripper, scrubbed using a diluted solution of FloorworX Rinse and then sealed with three coats of FloorworX Silk Matt or Gloss Sealer.



For more information please contact the **FloorworX TECHNICAL DEPARTMENT** by sending your query to technical@floorworx.co.za