

 **AREAS OF USE**

EDUCATION
COMMERCIAL
HEALTHCARE

HOSPITALITY
LEISURE
CORPORATE



SUGGESTED SPECIFICATION

IQ EMINENT SHEETING

Supply and fix 2.0mm thick x 2.0m wide iQ Eminent homogeneous vinyl sheeting with PUR reinforced surface treatment, manufactured in accordance with EN 649 and laid in FloorworX No. 62 acrylic adhesive which has been spread using a trowel fitted with an A2 notched blade at a rate of between 5.5m² and 6.5m² per litre on a previously prepared Class 1 sub-floor in accordance with SANS 10070, using a reliable Self-Leveller when required, including all cutting and waste. The sheeting must be rolled in both directions with an articulated 68kg three-sectional roller immediately after it has been laid into the adhesive. Joints must be butted, grooved and heat welded using the manufacturer's colour-matched multi-colour welding rod, ensuring that the welding rod bonds to more than 70% of the sheet thickness.

IQ EMINENT TILES

Supply and fix 2.0mm thick x 610mm X 610mm iQ Eminent homogeneous vinyl tiles with PUR reinforced surface treatment, manufactured in accordance with EN 649 and laid in FloorworX No. 62 acrylic adhesive which has been spread using a trowel fitted with an A2 notched blade at a rate of between 5.5m² and 6.5m² per litre on a previously prepared Class 1 sub-floor in accordance with SANS 10070, using a reliable Self-Leveller when required, including all cutting and waste. The flooring must be rolled in both directions with an articulated 68kg three-sectional roller immediately after it has been laid into the adhesive. Joints must be butted, grooved and heat welded (optional) using the manufacturer's colour-matched multi-colour welding rod, ensuring that the welding rod bonds to more than 70% of the sheet thickness.



For more information please contact the **FloorworX TECHNICAL DEPARTMENT** by sending your query to technical@floorworx.co.za